

単位 mm

呼び Nom Size d	D		H		B		m		R ₁	N	da	R	K	ℓ	引張荷重 Tensile Load	
	最大 max	最小 min	最大 max	最小 min	最大 max	最小 min	最大 max	最小 min	参考 ref	約 approx	最大 max	最小 min	約 approx	全ねじ範囲 Fully Threaded	(kgf)	[N]
M3	5.5	5.2	2.15	1.85	2.046	2.006	1.55	1.25	3	0.4	3.6	0.1	0.6	6~20	530	[5, 200]
4	7.5	7.2	2.75	2.45	2.566	2.506	1.95	1.65	4.1	0.4	4.7	0.2	0.8	8~25	930	[9, 100]
5	9.5	9.1	3.55	3.25	3.066	3.006	2.55	2.25	5.2	0.5	5.7	0.2	0.9	10~30	1,500	[14, 710]
6	10.5	10.1	4.2	3.8	4.085	4.010	3.0	2.6	5.6	0.5	6.8	0.25	1	10~35	2,130	[20, 890]
8	14	13.5	5.2	4.8	5.085	5.010	3.7	3.3	7.5	0.8	9.2	0.4	1.2	10~40	3,880	[38, 050]
10	18	17.5	6.2	5.8	6.085	6.010	4.4	4.0	10	0.8	11.2	0.4	1.5	10~45	6,150	[60, 310]
12	21	20.4	7.25	6.75	8.103	8.013	5.1	4.7	11	0.8	14.2	0.6	2	16~50	8,900	[87, 280]

呼び Nom Size d	D		H		B		m	N	F		ℓ
	最大 max	最小 min	最大 max	最小 min	最大 max	最小 min	最小 min	参考 ref	最大 max	最小 min	全ねじ範囲(max) Fully Threaded
# 6	6.65	6.35	1.85	1.60	2.01	1.98	1.20	0.38	0.25	0.13	15.87 [5/8"]
# 8	7.92	7.57	2.21	1.96	2.42	2.38	1.32	0.38	0.38	0.25	19.05 [3/4"]
#10	9.17	8.81	2.57	2.31	3.23	3.18	1.78	0.51	0.38	0.25	25.40 [1"]
1/4	11.10	10.64	3.35	3.10	4.03	3.97	2.21	0.79	0.51	0.38	25.40 [1"]
5/16	13.89	13.39	4.22	3.86	4.83	4.76	2.67	0.79	0.51	0.38	25.40 [1"]
3/8	16.66	16.15	5.10	4.70	5.63	5.56	3.10	0.79	0.51	0.38	31.75 [1-1/4"]
1/2	22.23	21.62	6.73	6.22	8.03	7.94	4.45	1.17	0.76	0.51	50.80 [2"]
5/8	25.40	24.64	8.41	7.90	9.63	9.53	5.33	1.57	0.76	0.51	50.80 [2"]