

単位 mm

呼び Nom Size d	ピッチ Pitch P	ねじ部長さ Thread Length b	ds		dk		k		S		t	r	da	v
			最 大 max	最 小 min	最 大 max	最 小 min	最 大 max	最 小 min	最 大 max	最 小 min	最 小 min	最 小 min	最 大 max	最 大 max
M1.6	0.35	15	1.6	1.46	3.14	2.86	1.6	1.46	1.545	1.520	0.7	0.1	2	0.16
2	0.4	16	2	1.86	3.98	3.62	2	1.86	1.545	1.520	1	0.1	2.6	0.2
2.5	0.45	17	2.5	2.36	4.68	4.32	2.5	2.36	2.045	2.020	1.1	0.1	3.1	0.25
(2.6)	0.45	—	—	—	4.50	4.32	2.6	2.46	2.045	2.020	1.1	0.1	3.2	—
3	0.5	18	3	2.86	5.68	5.32	3	2.86	2.560	2.520	1.3	0.1	3.6	0.3
4	0.7	20	4	3.82	7.22	6.78	4	3.82	3.080	3.020	2	0.2	4.7	0.4
5	0.8	22	5	4.82	8.72	8.28	5	4.82	4.095	4.020	2.5	0.2	5.7	0.5
6	1	24	6	5.82	10.22	9.78	6	5.70	5.095	5.020	3	0.25	6.8	0.6
8	1.25	28	8	7.78	13.27	12.73	8	7.64	6.095	6.020	4	0.4	9.2	0.8
10	1.5	32	10	9.78	16.27	15.73	10	9.64	8.115	8.025	5	0.4	11.2	1
12	1.75	36	12	11.73	18.27	17.73	12	11.57	10.115	10.025	6	0.6	13.7	1.2
(14)	2	40	14	13.73	21.33	20.67	14	13.57	12.142	12.032	7	0.6	15.7	1.4
16	2	44	16	15.73	24.33	23.67	16	15.57	14.142	14.032	8	0.6	17.7	1.6
(18)	2.5	48	18	17.73	27.33	26.67	18	17.57	14.142	14.032	9	0.6	20.2	1.8
20	2.5	52	20	19.67	30.33	29.67	20	19.48	17.230	17.050	10	0.8	22.4	2
(22)	2.5	56	22	21.67	33.39	32.61	22	21.48	17.230	17.050	11	0.8	24.4	2.2
24	3	60	24	23.67	36.39	35.61	24	23.48	19.275	19.065	12	0.8	26.4	2.4
(27)	3	66	27	26.67	40.39	39.61	27	26.48	19.275	19.065	13.5	1	30.4	2.7
30	3.5	72	30	29.67	45.39	44.61	30	29.48	22.275	22.065	15.5	1	33.4	3
(33)	3.5	78	33	32.61	50.39	49.61	33	32.38	24.275	24.065	16.5	1	36.4	3.3
36	4	84	36	35.61	54.46	53.54	36	35.38	27.275	27.065	19	1	39.4	3.6
(39)	4	90	39	38.61	58.46	57.54	39	38.38	27.275	27.065	20	1	42.4	3.9
42	4.5	96	42	41.61	63.46	62.54	42	41.38	32.330	32.080	21	1.2	45.6	4.2
(45)	4.5	102	45	44.61	68.46	67.54	45	44.38	32.330	32.080	23	1.2	48.6	4.5
48	5	108	48	47.61	72.46	71.54	48	47.38	36.330	36.080	24	1.6	52.6	4.8
(52)	5	116	52	51.54	78.46	77.54	52	51.26	36.330	36.080	26	1.6	56.6	5.2

- 備考 1. 細目ねじもあります。  
2. 呼びに( )を付けたものは、なるべく用いない。  
3. M2.6は、JISに規定されていないものです。(全ねじのみ製作可能)